



HF series LV

All in one solar charge inverter

HF4835U80-145 HF4830U60-145
HF2430U60-100



Efficiency

- Advanced MPPT with up to 99.9% efficiency
- Multiple charge and discharge modes are available

Safety

- 360 degrees of security from hardware to software
- With IEC, SAA, cETL, FCC certification

all in one

- Support for many types of batteries
- Supports Li-ion battery BMS communication

Reliable

- Outputs high-quality pure sine wave AC power
- Reliable output for long periods at rated power

User-Friendly

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

Intelligent

- Exclusive Li-ion battery BMS dual activation
- Support for remote monitoring of operating parameters

MODEL	HF4835U80-145	HF4830U60-145	HF2430U60-100	CAN BE SET
INVERTER OUTPUT				
Rated Output Power	3,500W	3,000W	3,000W	
Max.Peak Power	6,000VA			
Rated Output Voltage	120Vac (L/N/PE single phase)			√
Load Capacity of Motors	2HP			
Rated AC Frequency	50Hz/60Hz			
Waveform	Pure Sine Wave			
Switch Time	10ms (typical)			
BATTERY				
Battery Type	Li-ion/Lead-Acid/User Defined			√
Rated Battery Voltage	48Vdc		24Vdc	
Voltage Range	40~60Vdc		20~33Vdc	√
Max.MPPT Charging Current	80A		60A	√
Max.Mains/Generator Charging Current	40A			√
Max.Hybrid Charging Current	120A		100A	√
PV INPUT				
Num. of MPPT Trackers	1			
Max.PV Array Power	4,400W	3,400W	1,600W	
Max.Input Current	50A		40A	
Max.Voltage of Open Circuit	145Vdc		100Vdc	
MPPT Voltage Range	60~115Vdc		30~85Vdc	
MAINS/GENERATOR INPUT				
Input Voltage Range	90~140Vac			√
Frequency Range	50Hz/60Hz			√
Bypass Overload Current	40A			
EFFICIENCY				
MPPT Tracking Efficiency	99.9%			
Max. Battery Inverter Efficiency	92%			
GENERAL				
Dimensions	426*322*124mm (1.3*1*0.4ft)	378*280*103mm (1.2*0.9*0.3ft)		
Weight	10.8kg (23.8lb)	6.2kg (13.6lb)	6.8kg (14.9lb)	
Protection Degree	IP20, Indor Only			
Operating Temperature Range	-15°C~55°C (5°F~55°F)			
Noise	<60dB			
Cooling Method	Internal Fan			
Warranty	2 years			
COMMUNICATION				
Embedded Interfaces	RS485/CAN/USB/Dry contact			
External Modules (Optional)	Wi-Fi/GPRS			